

## 240 Series

select	Inquiry Designation		Principal Dimensions(mm)					rs min	Weight (kg)	Basic Load Ratings(KN)		Limited Speed(rpm)	PU
			d	D	B	b	Dynamic(Cr)			Static(Cor)	Grease		
24024	120	180	60	5,5	2	5.45	430	670	2000	3400	68		
24024K30	120	180	60	2	390	670	1500	2300	5.39	3400	68		
24024K30W33C3	120	180	60	2	390	670	1500	2300	5.39	3400	68		
24024W33C3	120	180	60	2	390	670	1500	2300	5.48	3400	68		
24026	130	200	69	5.5	2	8.05	540	815	1900	3000	81.5		
24026K30	130	200	69	2	505	895	1300	2100	7.95	3000	81.5		
24026K30W33C3	130	200	69	2	505	895	1300	2100	7.95	3000	81.5		
24026W33C3	130	200	69	2	505	895	1300	2100	8.08	3000	81.5		
24028	140	210	69	5.5	2	8.55	570	900	1800	2800	88		
24028K30	140	210	69	2	510	945	1200	1900	8.43	2800	88		
24028K30W33C3	140	210	69	2	510	945	1200	1900	8.43	2800	88		
24028W33C3	140	210	69	2	510	945	1200	1900	8.57	2800	88		
24030	150	225	75	5.5	2.1	10.5	655	1040	1700	2600	100		
24030K30	150	225	75	2.1	585	1060	1200	1800	10.5	2600	100		
24030K30W33C3	150	225	75	2.1	585	1060	1200	1800	10.5	2600	100		
24030W33C3	150	225	75	2.1	585	1060	1200	1800	10.7	2600	100		
24032	160	240	80	8.3	2.1	13.0	750	1200	1700	2400	114		
24032K30	160	240	80	2.1	650	1200	1100	1700	12.8	2400	114		
24032K30W33C3	160	240	80	2.1	650	1200	1100	1700	12.8	2400	114		
24032W33C3	160	240	80	2.1	650	1200	1100	1700	13	2400	114		
24034	170	260	90	8.3	2.1	17.5	930	1460	1400	2400	137		
24034K30	170	260	90	2.1	800	1470	1000	1600	17.4	2400	137		
24034K30W33C3	170	260	90	2.1	800	1470	1000	1600	17.4	2400	137		
24034W33C3	170	260	90	2.1	800	1470	1000	1600	17.7	2400	137		
24036	180	280	100	8.3	2.1	23.0	1080	1730	1500	2200	156		
24036K30	180	280	100	2.1	965	1770	950	1500	22.9	2200	156		
24036K30W33C3	180	280	100	2.1	965	1770	950	1500	22.9	2200	156		
24036W33C3	180	280	100	2.1	965	1770	950	1500	23.3	2200	156		
24038	190	290	100	8.3	2.1	24.5	1120	1800	1400	2000	163		
24038K30	190	290	100	2.1	995	1850	900	1400	23.9	2000	163		