

HK...RS Series

select	Inquiry Designation		Principal Dimensions(mm)				Cr (N)	Cor (N)	Fatigue loading Cu (N)	Limiting speed U/min	Weight (g)
			FW	D	C	r					
HK0810-RS	8	12	10	0.4	2750	2600	290	20000	3		
HK09X13X12-RS	8	13	12		3800	4300		19000	4		
HK1012-RS	16	22	14	0.8	7600	9700	1160	11000	13		
HK1214-RS	12	18	14	0.8	6500	7300	860	14000	10		
HK13X19X12-RS	13	19	12		6800	7580		12000	8.9		
HK1414-RS	14	20	14	0.8	7100	8500	1010	12000	12		
HK1514-RS	15	21	14	0.8	7800	9800	1190	11000	12		
HK1518-RS	15	21	18	0.8	10500	14400	1780	11000	16		
HK1614-RS	16	22	14	0.8	7600	9700	1160	11000	13		
HK17X25X14-RS	17	25	14		8000	9800		10000	17.7		
HK17X25X15.5-RS	17	25	15.5		9320	10400		13000	20		
HK17X25X20-RS	17	25	20		11600	13200		13000	26.2		
HK1814-RS	18	24	14	0.8	8100	10900	1300	9500	14		
HK2012-RS	20	26	12		9500	11900		9200	11.7		
HK2018-RS	20	26	18	0.8	12700	20100	2500	8500	21		
HK20X29X18-RS	20	29	18		8700	9980		7800	28.8		
HK2212-RS	22	28	12		8310	10000		9000	14		
HK2214-RS	22	28	14	0.8	9100	13400	1600	8000	16		
HK2218-RS	22	28	18		10400	20100		7800	23.5		
HK2518-RS	15	21	18	0.8	10500	14400	1780	11000	16		
HK3018-RS	30	37	18	0.8	17200	29000	3750	6000	37		
HK3518-RS	35	45	18	0.8	18700	33500	4400	5000	39		
HK4018-RS	40	47	18	0.8	20000	38500	5000	4500	45		
HK4518-RS	45	52	18	0.8	21300	43000	5700	4000	50		
HK5022-RS	50	58	22	0.8	31000	63000	8200	3600	76		
HK0812-RS	8	12	12	0.4	3800	3950	500	20000	3.1		
HK2818-RS	28	35	18	0.8	16400	26500	3450	6000	31		