

S 30 K Series

select	Inquiry Designation	Dimensions in mm											weight	Adapter sleeve	Locating Ring	Felt	Cover		This product is available in the following versions		
		d	E	H	A	b	C	H1	I	S	S1	S2					S	S	Fixed bearing	Floating bearing	
S3024K	110 320	112	380	110	40	215	150	M 24	36	30	17 kg	23024 K/H 3024	FR 10/180	10 x 8,5 - 195	Dimensions according to DIN 5419	DK 128	For closed-end housing	S 3024K AF	S 3024K BF	S 3024K AL	S 3024K BL
S3026K	115 350	125	410	120	45	239	160	M 24	36	30	20 kg	23026 K/H 3026	FR 10/200	FR 10/200	Dimensions according to DIN 5419	DK 133	For closed-end housing	S 3026K AF	S 3026K BF	S 3026K AL	S 3026K BL
S3028K	125 350	140	410	120	45	260	170	M 24	36	30	25 kg	23028 K/H 3028	FR 10/210	14 x 11 - 225	Dimensions according to DIN 5419	DK 151	For closed-end housing	S 3028K AF	S 3028K BF	S 3028K AL	S 3028K BL
S3030K	135 380	150	460	130	45	278	180	M 24	36	30	29 kg	23030 K/H 3030	FR 10/225	4 x 11 - 240	Dimensions according to DIN 5419	DK 161	For closed-end housing	S 3030K AF	S 3030K BF	S 3030K AL	S 3030K BL
S3032K	140 39	150	470	130	50	288	190	M 24	36	30	37 kg	23032 K/H 3032	FR 10/240	14 x 11 - 250	Dimensions according to DIN 5419	DK 166	For closed-end housing	S 3032K AF	S 3032K BF	S 3032K AL	S 3032K BL
S3034K	150 450	160	540	160	55	320	205	M 30	48	36	45 kg	23034 K/H 3034	FR 10/260	16 x 12 - 270	Dimensions according to DIN 5419	DK 180	For closed-end housing	S 3034K AF	S 3034K BF	S 3034K AL	S 3034K BL
S3036K	160 470	170	550	160	55	340	210	M 30	48	36	65 kg	23036 K/H 3036	FR 10/280	16 x 12 - 285	Dimensions according to DIN 5419	DK 190	For closed-end housing	S 3036K AF	S 3036K BF	S 3036K AL	S 3036K BL
S3038K	170 470	170	550	160	55	353	220	M 30	48	36	67 kg	23038 K/H 3038	FR 10/290	16 x 12 - 300	Dimensions according to DIN 5419	DK 200	For closed-end housing	S 3038K AF	S 3038K BF	S 3038K AL	S 3038K BL
S3040K	180 515	180	610	170	60	373	235	M 30	48	36	72 kg	23040 K/H 3040	FR 10/310	16 x 12 - 315	Dimensions according to DIN 5419	DK 210	For closed-end housing	S 3040K AF	S 3040K BF	S 3040K AL	S 3040K BL
S3044K	200 580	200	690	190	70	408	255	M 36	50	42	98 kg	23044 K/H 3044	FR 10/340	16 x 12 - 350	Dimensions according to DIN 5419	DK 230	For closed-end housing	S 3044K AF	S 3044K BF	S 3044K AL	S 3044K BL
S3048K	220 610	210	720	200	75	433	265	M 36	50	42	110 kg	23048 K/H 3048	FR 10/360	16 x 12 - 380	Dimensions according to DIN 5419	DK 250	For closed-end housing	S 3048K AF	S 3048K BF	S 3048K AL	S 3048K BL
S3052K	240 680	240	820	220	80	485	285	M 45	70	52	148 kg	23052 K/H 3052	FR 10/400	16 x 12 - 410	Dimensions according to DIN 5419	DK 270	For closed-end housing	S 3052K AF	S 3052K BF	S 3052K AL	S 3052K BL
S3056K	260 720	250	860	230	80	505	295	M 45	70	52	165 kg	23056 K/H 3056	FR 10/420	16 x 12 - 445	Dimensions according to DIN 5419	DK 290	For closed-end housing	S 3056K AF	S 3056K BF	S 3056K AL	S 3056K BL
S3060K	280 780	280	920	260	90	565	320	M 36	50	42	205 kg	23056 K/H 3060	FR 10/440	16 x 12 - 470	Dimensions according to DIN 5419	DK 310	For closed-end housing	S 3060K AF	S 3060K BF	S 3060K AL	S 3060K BL
S3064K	300 800	280	940	260	90	570	320	M 36	50	42	235 kg	23064 K/H 3064	FR 10/460	16 x 12 - 505	Dimensions according to DIN 5419	DK 330	For closed-end housing	S 3064K AF	S 3064K BF	S 3064K AL	S 3064K BL
S3068K	320 860	300	1000	280	95	615	340	M 36	50	42	280 kg	23068 K/H 3068	FR 10/490	16 x 12 - 535	Dimensions according to DIN 5419	DK 360	For closed-end housing	S 3068K AF	S 3068K BF	S 3068K AL	S 3068K BL
S3072K	340 900	320	1060	280	95	655	345	M 36	50	42	340 kg	23072 K/H 3072	FR 10/510	16 x 12 - 565	Dimensions according to DIN 5419	DK 390	For closed-end housing	S 3072K AF	S 3072K BF	S 3072K AL	S 3072K BL
S3076K	360 900	330	1060	280	100	675	380	M 36	50	42	400 kg	23076 K/H 3076	FR 10/530	16 x 12 - 600	Dimensions according to DIN 5419	DK 410	For closed-end housing	S 3076K AF	S 3076K BF	S 3076K AL	S 3076K BL
S3080K	380 950	350	1100	325	120	715	400	M 36	50	42	460 kg	23080 K/H 3080	FR 10/550	16 x 12 - 630	Dimensions according to DIN 5419	DK 430	For closed-end housing	S 3080K AF	S 3080K BF	S 3080K AL	S 3080K BL
S3084K	400 980	375	1160	340	120	750	430	M 36	50	42	500 kg	23084 K/H 3084	FR 10/570	16 x 12 - 660	Dimensions according to DIN 5419	DK 470	For closed-end housing	S 3084K AF	S 3084K BF	S 3084K AL	S 3084K BL
S3088K	410 1020	390	1200	340	125	780	430	M 36	50	42	600 kg	23088 K/H 3088	FR 10/590	16 x 12 - 675	Dimensions according to DIN 5419	DK 490	For closed-end housing	S 3088K AF	S 3088K BF	S 3088K AL	S 3088K BL
S3092K	430 1080	400	1260	360	130	805	440	M 48	75	56	500 kg	23092 K/H 3092	FR 10/610	16 x 12 - 710	Dimensions according to DIN 5419	DK 510	For closed-end housing	S 3092K AF	S 3092K BF	S 3092K AL	S 3092K BL

S 30 K Series

S3096K	450	1180	410	1380	380	190	825	440	M 48	75	56	800 kg	23096 K/H 3096	FR 10/630	16 x 12 - 740	Dimensions according to DIN 5419	DK 530	For closed-end housing	S 3096K AF	S 3096K BF	S 3096K AL	S 3096K BL
--------	-----	------	-----	------	-----	-----	-----	-----	---------	----	----	-----------	----------------------	-----------	---------------------	---	-----------	------------------------------	------------------	------------------	------------------	------------------