

HBNDK Series

select	Inquiry Designation	Dimensions in mm																		weight	Adapter sleeve	Fixed Floating bearing bearing
		dm	h	n	d1	h1	a	b	g	g1	c	g2	g3	g4	k	u	v	t	s			
HBND2213K	185 80	40	60	155 mm	235 mm	70 mm	44 mm	100 mm	22 mm	120 mm	55 mm	39 mm	2 mm	15 mm	20 mm	135 mm	M 10	M 6	23 kg	H313	HBND2213K-AF	HBND2213K-AL
HBND2213K	185 80	40	60	155 mm	235 mm	70 mm	44 mm	100 mm	22 mm	120 mm	55 mm	39 mm	2 mm	15 mm	20 mm	135 mm	M 10	M 6	23 kg	H313	HBND2213K-BF	HBND2213K-BL
HBND2215K	225 90	45	65	180 mm	285 mm	85 mm	45 mm	105 mm	35 mm	125 mm	55 mm	44 mm	2 mm	20 mm	28 mm	155 mm	M 16	M 6	15 kg	H315	HBND2215K-AF	HBND2215K-AL
HBND2215K	225 90	45	65	180 mm	285 mm	85 mm	45 mm	105 mm	35 mm	125 mm	55 mm	44 mm	2 mm	20 mm	28 mm	155 mm	M 16	M 6	15 kg	H315	HBND2215K-BF	HBND2215K-BL
HBND2218K	290 110	60	80	220 mm	370 mm	110 mm	55 mm	104 mm	38 mm	123 mm	53 mm	45 mm	2 mm	23 mm	32 mm	185 mm	M 20	M 8	28 kg	H318	HBND2218K-AF	HBND2218K-AL
HBND2218K	290 110	60	80	220 mm	370 mm	110 mm	55 mm	104 mm	38 mm	123 mm	53 mm	45 mm	2 mm	23 mm	32 mm	185 mm	M 20	M 8	28 kg	H318	HBND2218K-BF	HBND2218K-BL
HBND2220K	320 130	65	90	255 mm	400 mm	120 mm	65 mm	141 mm	40 mm	168 mm	78 mm	57 mm	2.5 mm	30 mm	35 mm	205 mm	M 24	M 8	30 kg	H30K	HBND2220K-AF	HBND2220K-AL
HBND2220K	320 130	65	90	255 mm	400 mm	120 mm	65 mm	141 mm	40 mm	168 mm	78 mm	57 mm	2.5 mm	30 mm	35 mm	205 mm	M 24	M 8	30 kg	H30K	HBND2220K-BF	HBND2220K-BL
HBND2222K	350 140	70	100	280 mm	440 mm	130 mm	73 mm	149,2 mm	42 mm	172mm	82,6 mm	60 mm	2.5 mm	30 mm	35 mm	130 mm	M 24	M12	50 kg	H32K	HBND2222K-AF	HBND2222K-AL
HBND2222K	350 140	70	100	280 mm	440 mm	130 mm	73 mm	149,2 mm	42 mm	172mm	82,6 mm	60 mm	2.5 mm	30 mm	35 mm	130 mm	M 24	M12	50 kg	H32K	HBND2222K-BF	HBND2222K-BL
HBND3122K	300 130	80	100	263 mm	400 mm	140 mm	80 mm	146 mm	40 mm	171 mm	78 mm	62 mm	2.5mm	25 mm	35 mm	215 mm	M 20	M 12	40 kg	H322K	HBND3122K-AF	HBND3122K-AL
HBND3122K	300 130	80	100	263 mm	400 mm	140 mm	80 mm	146 mm	40 mm	171 mm	78 mm	62 mm	2.5mm	25 mm	35 mm	215 mm	M 20	M 12	40 kg	H322K	HBND3122K-BF	HBND3122K-BL
HBND3222K	350 140	70	100	280 mm	440 mm	130 mm	89,8 mm	166 mm	42 mm	94 mm	91 mm	68 mm	2.5 mm	30 mm	35 mm	230 mm	M 24	M 12	35 kg	H2322	HBND3222K-AF	HBND3222K-AL
HBND3222K	350 140	70	100	280 mm	440 mm	130 mm	89,8 mm	166 mm	42 mm	94 mm	91 mm	68 mm	2.5 mm	30 mm	35 mm	230 mm	M 24	M 12	35 kg	H2322	HBND3222K-BF	HBND3222K-BL
HBND2224K	370 150	75	110	300 mm	470 mm	140 mm	77 mm	143 mm	42 mm	168 mm	74 mm	61 mm	2.5 mm	30 mm	35 mm	245 mm	M 24	M 12	58 kg	H3124	HBND2224K-AF	HBND2224K-AL
HBND2224K	370 150	75	110	300 mm	470 mm	140 mm	77 mm	143 mm	42 mm	168 mm	74 mm	61 mm	2.5 mm	30 mm	35 mm	245 mm	M 24	M 12	58 kg	H3124	HBND2224K-BF	HBND2224K-BL
HBND3024K	300 115	60	110	230 mm	370 mm	110 mm	60 mm	126 mm	35 mm	146 mm	63 mm	57 mm	2.5 mm	25 mm	35 mm	205 mm	M 20	M 8	20 kg	H324K	HBND3024K-AF	HBND3024K-AL
HBND3024K	300 115	60	110	230 mm	370 mm	110 mm	60 mm	126 mm	35 mm	146 mm	63 mm	57 mm	2.5 mm	25 mm	35 mm	205 mm	M 20	M 8	20 kg	H324K	HBND3024K-BF	HBND3024K-BL
HBND3224K	370 150	75	110	300 mm	470 mm	140 mm	95 mm	161 mm	42 mm	186 mm	83 mm	70 mm	2.5 mm	30 mm	35 mm	245 mm	M 24	M 12	40 kg	H2324	HBND3224K-AF	HBND3224K-AL
HBND3224K	370 150	75	110	300 mm	470 mm	140 mm	95 mm	161 mm	42 mm	186 mm	83 mm	70 mm	2.5 mm	30 mm	35 mm	245 mm	M 24	M 12	40 kg	H2324	HBND3224K-BF	HBND3224K-BL
HBND2226K	400 160	85	115	315 mm	500 mm	150 mm	84 mm	182 mm	45 mm	202 mm	95 mm	69 mm	3 mm	30 mm	35 mm	260 mm	M 24	M 12	65 kg	H3126	HBND2226K-AF	HBND2226K-AL
HBND2226K	400 160	85	115	315 mm	500 mm	150 mm	84 mm	182 mm	45 mm	202 mm	95 mm	69 mm	3 mm	30 mm	35 mm	260 mm	M 24	M 12	65 kg	H3126	HBND2226K-BF	HBND2226K-BL
HBND3026K	340 130	60	115	260 mm	410 mm	120 mm	70 mm	133 mm	38 mm	156 mm	68 mm	59 mm	2 mm	25 mm	35 mm	225 mm	M 20	M10	30 kg	H326K	HBND3026K-AF	HBND3026K-AL
HBND3026K	340 130	60	115	260 mm	410 mm	120 mm	70 mm	133 mm	38 mm	156 mm	68 mm	59 mm	2 mm	25 mm	35 mm	225 mm	M 20	M10	30 kg	H326K	HBND3026K-BF	HBND3026K-BL
HBND3126K	350 145	80	115	295 mm	430 mm	150 mm	90 mm	165 mm	40 mm	190 mm	85 mm	72 mm	3 mm	25 mm	35 mm	245 mm	M 20	M 12	55 kg	H326K	HBND3126K-AF	HBND3126K-AL
HBND3126K	350 145	80	115	295 mm	430 mm	150 mm	90 mm	165 mm	40 mm	190 mm	85 mm	72 mm	3 mm	25 mm	35 mm	245 mm	M 20	M 12	55 kg	H326K	HBND3126K-BF	HBND3126K-BL
HBND3226K	400 160	85	115	315 mm	500 mm	150 mm	100 mm	188 mm	45 mm	218 mm	103 mm	77 mm	3 mm	30 mm	35 mm	260 mm	M 24	M 12	50 kg	H2326	HBND3226K-AF	HBND3226K-AL
HBND3226K	400 160	85	115	315 mm	500 mm	150 mm	100 mm	188 mm	45 mm	218 mm	103 mm	77 mm	3 mm	30 mm	35 mm	260 mm	M 24	M 12	50 kg	H2326	HBND3226K-BF	HBND3226K-BL
HBND2228K	430 170	85	125	345 mm	530 mm	160 mm	88 mm	166 mm	50 mm	196 mm	88 mm	70 mm	3 mm	30 mm	35 mm	285 mm	M 24	M 16	70 kg	H3128	HBND2228K-AF	HBND2228K-AL
HBND2228K	430 170	85	125	345 mm	530 mm	160 mm	88 mm	166 mm	50 mm	196 mm	88 mm	70 mm	3 mm	30 mm	35 mm	285 mm	M 24	M 16	70 kg	H3128	HBND2228K-BF	HBND2228K-BL