

HFO 200 Series



select Inquiry Designation			E	H	M	A	B	B1	C	d1	Dimensions in mm				L	L1	S	S1	U	V	d	weight	shaft nut	locking plate	Fixed bearing	floating bearing
											d2	H1	K	K1												
HFO 217	85	260	125	60	330 mm	182 mm	110 mm	35 mm	83 mm	96 mm	230 mm	90 mm	105 mm	180 mm	165 mm	M 20	5 mm	24 mm	40 mm	33 kg	KM 17	MB 17	HFO 217 AF	HFO 217 AL		
HFO 217	85	260	125	60	330 mm	182 mm	110 mm	35 mm	83 mm	96 mm	230 mm	90 mm	105 mm	180 mm	165 mm	M 20	5 mm	24 mm	40 mm	33 kg	KM 17	MB 17	HFO 217 BF	HFO 217 BL		
HFO 218	90	290	135	70	360 mm	190 mm	120 mm	45 mm	88 mm	100 mm	245 mm	95 mm	112 mm	190 mm	170 mm	M 20	5 mm	24 mm	40 mm	42 kg	KM 18	MB 18	HFO 218 AF	HFO 218 AL		
HFO 218	90	290	135	70	360 mm	190 mm	120 mm	45 mm	88 mm	100 mm	245 mm	95 mm	112 mm	190 mm	170 mm	M 20	5 mm	24 mm	40 mm	42 kg	KM 18	MB 18	HFO 218 BF	HFO 218 BL		
HFO 219	95	290	140	80	360 mm	210 mm	135 mm	40 mm	93 mm	105 mm	255 mm	100 mm	118 mm	200 mm	184 mm	M 20	5 mm	24 mm	40 mm	45 kg	KM 19	MB 19	HFO 219 AF	HFO 219 AL		
HFO 219	95	290	140	80	360 mm	210 mm	135 mm	40 mm	93 mm	105 mm	255 mm	100 mm	118 mm	200 mm	184 mm	M 20	5 mm	24 mm	40 mm	45 kg	KM 19	MB 19	HFO 219 BF	HFO 219 BL		
HFO 220	100	320	145	75	400 mm	205 mm	130 mm	50 mm	98 mm	110 mm	270 mm	103 mm	123 mm	206 mm	186 mm	M 24	5 mm	28 mm	45 mm	55 kg	KM 20	MB 20	HFO 220 AF	HFO 220 AL		
HFO 220	100	320	145	75	400 mm	205 mm	130 mm	50 mm	98 mm	110 mm	270 mm	103 mm	123 mm	206 mm	186 mm	M 24	5 mm	28 mm	45 mm	55 kg	KM 20	MB 20	HFO 220 BF	HFO 220 BL		
HFO 222	110	350	160	75	420 mm	216 mm	145 mm	50 mm	108 mm	120 mm	290 mm	114,5 mm	138 mm	229 mm	203 mm	M 24	5 mm	28 mm	45 mm	70 kg	KM 22	MB 22	HFO 222 AF	HFO 222 AL		
HFO 222	110	350	160	75	420 mm	216 mm	145 mm	50 mm	108 mm	120 mm	290 mm	114,5 mm	138 mm	229 mm	203 mm	M 24	5 mm	28 mm	45 mm	70 kg	KM 22	MB 22	HFO 222 BF	HFO 222 BL		
HFO 224	120	347	170	90	420 mm	245 mm	170 mm	55 mm	118 mm	135 mm	315 mm	138 mm	164 mm	276 mm	240 mm	M 24	8 mm	28 mm	45 mm	95 kg	KM 24	MB 24	HFO 224 AF	HFO 224 AL		
HFO 224	120	347	170	90	420 mm	245 mm	170 mm	55 mm	118 mm	135 mm	315 mm	138 mm	164 mm	276 mm	240 mm	M 24	8 mm	28 mm	45 mm	95 kg	KM 24	MB 24	HFO 224 BF	HFO 224 BL		
HFO 226	130	377	180	100	450 mm	260 mm	180 mm	60 mm	128 mm	145 mm	335 mm	135 mm	164 mm	270 mm	240 mm	M 24	8 mm	28 mm	45 mm	100 kg	KM 26	MB 26	HFO 226 AF	HFO 226 AL		
HFO 226	130	377	180	100	450 mm	260 mm	180 mm	60 mm	128 mm	145 mm	335 mm	135 mm	164 mm	270 mm	240 mm	M 24	8 mm	28 mm	45 mm	100 kg	KM 26	MB 26	HFO 226 BF	HFO 226 BL		
HFO 228	140	415	190	100	500 mm	265 mm	190 mm	65 mm	138 mm	160 mm	355 mm	140 mm	170 mm	280 mm	250 mm	M 30	8 mm	35 mm	45 mm	125 kg	KM 29	MB 29	HFO 228 AF	HFO 228 AL		
HFO 228	140	415	190	100	500 mm	265 mm	190 mm	65 mm	138 mm	160 mm	355 mm	140 mm	170 mm	280 mm	250 mm	M 30	8 mm	35 mm	45 mm	125 kg	KM 29	MB 29	HFO 228 BF	HFO 228 BL		
HFO 230	150	450	200	115	540 mm	265 mm	190 mm	65 mm	148 mm	170 mm	375 mm	140 mm	173 mm	280 mm	250 mm	M 30	8 mm	35 mm	50 mm	140 kg	KM 30	MB 30	HFO 230 AF	HFO 230 AL		
HFO 230	150	450	200	115	540 mm	265 mm	190 mm	65 mm	148 mm	170 mm	375 mm	140 mm	173 mm	280 mm	250 mm	M 30	8 mm	35 mm	50 mm	140 kg	KM 30	MB 30	HFO 230 BF	HFO 230 BL		
HFO 232	160	470	215	120	560 mm	380 mm	205 mm	65 mm	158 mm	178 mm	405 mm	158 mm	193 mm	316 mm	280 mm	M 30	10 mm	35 mm	50 mm	165 kg	KM 32	MB 32	HFO 232 AF	HFO 232 AL		
HFO 232	160	470	215	120	560 mm	380 mm	205 mm	65 mm	158 mm	178 mm	405 mm	158 mm	193 mm	316 mm	280 mm	M 30	10 mm	35 mm	50 mm	165 kg	KM 32	MB 32	HFO 232 BF	HFO 232 BL		
HFO 234	170	515	235	130	610 mm	310 mm	230 mm	70 mm	168 mm	195 mm	440 mm	175 mm	213 mm	350 mm	310 mm	M 30	10 mm	35 mm	55 mm	215 kg	KM 34	MB 34	HFO 234 AF	HFO 234 AL		
HFO 234	170	515	235	130	610 mm	310 mm	230 mm	70 mm	168 mm	195 mm	440 mm	175 mm	213 mm	350 mm	310 mm	M 30	10 mm	35 mm	55 mm	215 kg	KM 34	MB 34	HFO 234 BF	HFO 234 BL		
HFO 236	180	545	245	150	650 mm	320 mm	240 mm	75 mm	177 mm	205 mm	455 mm	180 mm	218 mm	360 mm	320 mm	M 30	10 mm	35 mm	65 mm	235 kg	KM 36	MB 36	HFO 236 AF	HFO 236 AL		
HFO 236	180	545	245	150	650 mm	320 mm	240 mm	75 mm	177 mm	205 mm	455 mm	180 mm	218 mm	360 mm	320 mm	M 30	10 mm	35 mm	65 mm	235 kg	KM 36	MB 36	HFO 236 BF	HFO 236 BL		
HFO 240	200	600	275	160	730 mm	350 mm	260 mm	85 mm	198 mm	227 mm	510 mm	189 mm	233 mm	377 mm	338 mm	M 36	12 mm	42 mm	70 mm	320 kg	KM 40	MB 40	HFO 240 AF	HFO 240 AL		
HFO 240	200	600	275	160	730 mm	350 mm	260 mm	85 mm	198 mm	227 mm	510 mm	189 mm	233 mm	377 mm	338 mm	M 36	12 mm	42 mm	70 mm	320 kg	KM 40	MB 40	HFO 240 BF	HFO 240 BL		
HFO 244	220	670	304	180	820 mm	370 mm	280 mm	95 mm	218 mm	255 mm	565 mm	202 mm	251 mm	404 mm	365 mm	M 36	12 mm	42 mm	80 mm	375 kg	KM 44	MB 44	HFO 244 AF	HFO 244 AL		
HFO 244	220	670	304	180	820 mm	370 mm	280 mm	95 mm	218 mm	255 mm	565 mm	202 mm	251 mm	404 mm	365 mm	M 36	12 mm	42 mm	80 mm	375 kg	KM 44	MB 44	HFO 244 BF	HFO 244 BL		