

HFO 500 Series

select Inquiry Designation			Dimensions in mm															weight	Adapter sleeve	Fixed bearing	Floating bearing
			d	E	H	M	A	B	B1	C	d2	H1	L	L1	S	S1	U				
HFO 517	75	260	125	60	330 mm	182 mm	110 mm	35 mm	96 mm	230 mm	180 mm	165 mm	M 20 mm	5 mm	24 mm	40 mm	43 kg	H 317	HFO 517 AF	HFO 517 AL	
HFO 517	75	260	125	60	330 mm	182 mm	110 mm	35 mm	96 mm	230 mm	180 mm	165 mm	M 20 mm	5 mm	24 mm	40 mm	43 kg	H 317	HFO 517 BF	HFO 517 BL	
HFO 518	80	290	135	70	360 mm	190 mm	120 mm	45 mm	100 mm	245 mm	190 mm	170 mm	M 20 mm	5 mm	24 mm	40 mm	45 kg	H 318	HFO 518 AF	HFO 518 AL	
HFO 518	80	290	135	70	360 mm	190 mm	120 mm	45 mm	100 mm	245 mm	190 mm	170 mm	M 20 mm	5 mm	24 mm	40 mm	45 kg	H 318	HFO 518 BF	HFO 518 BL	
HFO 519	85	290	140	80	360 mm	210 mm	135 mm	40 mm	105 mm	255 mm	200 mm	184 mm	M 20 mm	5 mm	24 mm	40 mm	45 kg	H319	HFO 519 AF	HFO 519 AL	
HFO 519	85	290	140	80	360 mm	210 mm	135 mm	40 mm	105 mm	255 mm	200 mm	184 mm	M 20 mm	5 mm	24 mm	40 mm	45 kg	H319	HFO 519 BF	HFO 519 BL	
HFO 520	90	320	145	75	400 mm	205 mm	130 mm	50 mm	110 mm	270 mm	206 mm	186 mm	M 24 mm	5 mm	28 mm	45 mm	57 kg	H 322	HFO 520 AF	HFO 520 AL	
HFO 520	90	320	145	75	400 mm	205 mm	130 mm	50 mm	110 mm	270 mm	206 mm	186 mm	M 24 mm	5 mm	28 mm	45 mm	57 kg	H 322	HFO 520 BF	HFO 520 BL	
HFO 522	100	350	160	75	420 mm	216 mm	145 mm	50 mm	120 mm	290 mm	229 mm	203 mm	M 24 mm	5 mm	28 mm	45 mm	73 kg	H 322	HFO 522 AF	HFO 522 AL	
HFO 522	100	350	160	75	420 mm	216 mm	145 mm	50 mm	120 mm	290 mm	229 mm	203 mm	M 24 mm	5 mm	28 mm	45 mm	73 kg	H 322	HFO 522 BF	HFO 522 BL	
HFO 524	110	347	170	90	420 mm	245 mm	170 mm	55 mm	135 mm	315 mm	276 mm	240 mm	M 24 mm	8 mm	28 mm	45 mm	102 kg	H 3124	HFO 524 AF	HFO 524 AL	
HFO 524	110	347	170	90	420 mm	245 mm	170 mm	55 mm	135 mm	315 mm	276 mm	240 mm	M 24 mm	8 mm	28 mm	45 mm	102 kg	H 3124	HFO 524 BF	HFO 524 BL	
HFO 526	115	377	180	100	450 mm	260 mm	180 mm	60 mm	145 mm	335 mm	270 mm	240 mm	M 24 mm	8 mm	28 mm	45 mm	105 kg	H3126	HFO 526 AF	HFO 526 AL	
HFO 526	115	377	180	100	450 mm	260 mm	180 mm	60 mm	145 mm	335 mm	270 mm	240 mm	M 24 mm	8 mm	28 mm	45 mm	105 kg	H3126	HFO 526 BF	HFO 526 BL	
HFO 528	125	415	190	100	500 mm	265 mm	190 mm	65 mm	160 mm	355 mm	280 mm	250 mm	M 30 mm	8 mm	35 mm	45 mm	150 kg	H 3128	HFO 528 AF	HFO 528 AL	
HFO 528	125	415	190	100	500 mm	265 mm	190 mm	65 mm	160 mm	355 mm	280 mm	250 mm	M 30 mm	8 mm	35 mm	45 mm	150 kg	H 3128	HFO 528 BF	HFO 528 BL	
HFO 532	140	470	215	120	560 mm	280 mm	205 mm	65 mm	178 mm	405 mm	316 mm	280 mm	M 30 mm	10 mm	35 mm	50 mm	180 kg	H 3132	HFO 532 AF	HFO 532 AL	
HFO 532	140	470	215	120	560 mm	280 mm	205 mm	65 mm	178 mm	405 mm	316 mm	280 mm	M 30 mm	10 mm	35 mm	50 mm	180 kg	H 3132	HFO 532 BF	HFO 532 BL;	
HFO 534	150	515	235	130	610 mm	310 mm	230 mm	70 mm	195 mm	440 mm	350 mm	310 mm	M 30 mm	10 mm	35 mm	55 mm	225 kg	H 3134	HFO 534 AF	HFO 534 AL	
HFO 534	150	515	235	130	610 mm	310 mm	230 mm	70 mm	195 mm	440 mm	350 mm	310 mm	M 30 mm	10 mm	35 mm	55 mm	225 kg	H 3134	HFO 534 BF	HFO 534 BL	
HFO 536	160	545	245	150	650 mm	320 mm	240 mm	75 mm	205 mm	455 mm	360 mm	320 mm	M 30 mm	10 mm	35 mm	65 mm	255 kg	H 3136	HFO 536 AF	HFO 536 AL	
HFO 536	160	545	245	150	650 mm	320 mm	240 mm	75 mm	205 mm	455 mm	360 mm	320 mm	M 30 mm	10 mm	35 mm	65 mm	255 kg	H 3136	HFO 536 BF	HFO 536 BL	
HFO 540	180	600	275	160	730 mm	350 mm	260 mm	85 mm	227 mm	510 mm	3778 mm	338 mm	M 36 mm	12 mm	42 mm	70 mm	340 kg	H 3140	HFO 540 AF	HFO 540 AL	
HFO 540	180	600	275	160	730 mm	350 mm	260 mm	85 mm	227 mm	510 mm	3778 mm	338 mm	M 36 mm	12 mm	42 mm	70 mm	340 kg	H 3140	HFO 540 BF	HFO 540 BL	
HFO 544	200	670	305	180	820 mm	370 mm	280 mm	95 mm	255 mm	565 mm	404 mm	365 mm	M 36 mm	12 mm	42 mm	80 mm	395 kg	H3144	HFO 544 AF	HFO 544 AL	

HFO 500 Series

HFO 544	200	670	305	180	820 mm	370 mm	280 mm	95 mm	255 mm	565 mm	404 mm	365 mm	M 36 mm	12 mm	42 mm	80 mm	395 kg	H3144	HFO 544 BF	HFO 544 BL	
------------	-----	-----	-----	-----	-----------	-----------	-----------	----------	--------	--------	--------	-----------	---------------	----------	----------	----------	-----------	-------	------------------	------------------	--